



DRIFIRE® HIGH PERFORMANCE FR HI-VIS KNIT BUTTON UP SHIRT CLASS 3

■ ISHAT29RT (Fluorescent Yellow)

- FUZE odor control
- Permanent moisture wicking technology, breathable

ARC RATING: 16 cal/cm² | CAT 2 SIZE: SM-3X, RG | MD-3X, TL
COMPLIANT WITH: ANSI/ISEA 107 TYPE R CLASS 3, ASTM F1506,
CSA Z462, NFPA® 70E, NFPA® 2112, OSHA 1910.269

MATERIAL: 6.95 oz. Inherently FR Lightweight Fabric



DRIFIRE® DH FR HI-VIS WORK SHIRT CLASS 3

■ ISH65DH29RT (Fluorescent Yellow)

- Pleated back, drop shoulder design
- Moisture wicking technology, breathable
- Rounded back shirt tail

ARC RATING: 8.9 cal/cm² | CAT 2 SIZE: SM-3X, RG | MD-3X, TL
COMPLIANT WITH: ANSI/ISEA 107 TYPE R CLASS 3, ASTM F1506,
CSA Z462, NFPA® 70E, NFPA® 2112, OSHA 1910.269

MATERIAL: 6.5 oz. Westex® DH



DRIFIRE® HIGH PERFORMANCE FR HI-VIS LONG SLEEVE HENLEY CLASS 3

■ HSAT29RT (Fluorescent Yellow)

- Flat-locked seams to reduce chafing
- Permanent moisture wicking & breathable

ARC RATING: 16 cal/cm² | CAT 2

SIZE: SM-3X, RG | MD-3X, TL

COMPLIANT WITH: ANSI/ISEA 107 TYPE R CLASS 3, ASTM F1506, CSA Z462, NFPA® 70E,
NFPA® 2112, OSHA 1910.269

MATERIAL: 6.95 oz. Inherently FR
Lightweight Fabric



DRIFIRE® HIGH PERFORMANCE FR LONG SLEEVE T-SHIRT CLASS 3

■ LSCAT29RT (Fluorescent Yellow)

- Permanent moisture wicking technology
- Flat-locked seams reduces chafing
from fall protection gear

ARC RATING: 16 cal/cm² | CAT 2

SIZE: SM-3X, RG | MD-3X, TL

COMPLIANT WITH: ANSI/ISEA 107 TYPE R CLASS 3, ASTM F1506, CSA Z462, NFPA® 70E,
NFPA® 2112, OSHA 1910.269

MATERIAL: 6.95 oz. Inherently FR
Lightweight Fabric



DRIFIRE® HYPERLITE FR HI-VIS LONG SLEEVE T-SHIRT CLASS 3

■ LSC57AT29RT (Fluorescent Yellow)

- FUZE odor control
- UPF rated 50+ sun protection
- Permanent moisture wicking & breathable

ARC RATING: 9 cal/cm² | CAT 2

SIZE: SM-3X, RG | MD-3X, TL

COMPLIANT WITH: ANSI/ISEA 107 TYPE R CLASS 3, ASTM F1506, CSA Z462, NFPA® 70E,
NFPA® 2112, OSHA 1910.269

MATERIAL: 5.7 oz. Inherently AR/FR
Hyper-lite Weight Fabric



DRIFIRE® HIGH PERFORMANCE FR HI-VIS PULLOVER HOODIE CLASS 3

■ **IHDPANT29RT** (Fluorescent Yellow)

- Permanent moisture wicking technology
- Zippered cellphone pocket
- Three-piece hood with hidden drawstring

ARC RATING: 28 cal/cm² | CAT 3 **SIZE:** SM-3X, RG | MD-3X, TL

COMPLIANT WITH: ANSI/ISEA 107 TYPE R CLASS 3, ASTM F1506, CSA Z462, NFPA® 70E, NFPA® 2112, OSHA 1910.269

MATERIAL: 12.3 oz. Inherently FR Windproof and Water-Resistant Knit



DRIFIRE® HIGH PERFORMANCE FR PULLOVER HOODIE CLASS 3

■ **IHDP12ANT01** (Black)

- Permanent moisture wicking technology
- Zippered cellphone pocket
- Front hand warmer pockets

ARC RATING: 28 cal/cm² | CAT 3 **SIZE:** SM-3X, RG | MD-3X, TL

COMPLIANT WITH: ASTM F1506, CSA Z462, NFPA® 70E, NFPA® 2112, OSHA 1910.269

MATERIAL: 12.3 oz. Inherently FR Windproof and Water-Resistant Knit



DRIFIRE® HYPERLITE FR LONG SLEEVE T-SHIRT

■ **LSC57AT06** (Grey)

■ **LSC57AT13** (Navy)

- FUZE odor control
- UPF rated 50+ sun protection
- Permanent moisture wicking & breathable

ARC RATING: 9 cal/cm² | CAT 2

SIZE: SM-3X, RG | MD-3X, TL

COMPLIANT WITH: ASTM F1506, CSA Z462, NFPA® 70E, NFPA® 2112, OSHA 1910.269

MATERIAL: 5.7 oz. Inherently AR/FR Hyper-lite Weight Fabric



DRIFIRE® FR ANTI-STAT MESH CLASS 3 VEST WITH LANYARD PORT

■ **V10AM2023ZL** (Fluorescent Yellow)

- Non-conductive zip front closure
- Adjustable snap sleeves

ARC RATING: 5.2 cal/cm² | CAT 1

SIZE: SM-3X, RG

COMPLIANT WITH: ANSI/ISEA 107 TYPE R CLASS 3, ASTM F1506, CSA Z462, NFPA® 70E, OSHA 1910.269, Gas Probe Shirley Method 138:2000, EN 1149-3/2004 & EN 1149-5/2008

MATERIAL: 6 oz. Anti-Stat FR Mesh



DRIFIRE® FR MESH CLASS 3 VEST WITH LANYARD PORT

■ **V8AM2023ZL** (Fluorescent Yellow)

- Reinforced lanyard port
- Adjustable sleeve snaps

ARC RATING: 4.6 cal/cm² | CAT 1

SIZE: SM-3X, RG

COMPLIANT WITH: ANSI/ISEA 107 TYPE R CLASS 3, ASTM F1506, CSA Z462, NFPA® 70E, OSHA 1910.269

MATERIAL: 5.8 oz. FR Mesh