

POLARTEC FR CARE GUIDE

 POLARTEC[®]
POWER DRY[®] FR

 POLARTEC[®]
POWER GRID[™] FR




 POLARTEC[®]
WIND PRO[®] FR

POLARTEC FR CARE GUIDE

POLARTEC® POWER DRY® FR

Offering superior next-to-skin moisture management, Polartec® Power Dry® FR uses a patented tri-blend knit to deliver mechanical wicking action and high breathability for fast drying times and ultra-comfortable performance.



Polartec® Power Dry® FR Fabrics

STYLE	DESCRIPTION	CONTENT	NFPA 70E PPE CATEGORY	NFPA 2112 CERTIFIED	EN ISO 11612:2015	IEC 61482-2	CUTTABLE WIDTH	SPEC WEIGHT oz/yd ² (g/m ²)	LAUNDRY	TYPICAL GARMENT APPLICATIONS
0680/0681	4.5 oz Jersey Knit Base Layer	Patented Westex Tri-Blend Lenzing™ Lyocell, Modacrylic, Aramid	Cat 1	Yes			63 in	4.5 (152)		Base Layer Shirt
2009	6.4 oz Pique Knit	Patented Westex Tri-Blend Lenzing™ Lyocell, Modacrylic, Aramid	Cat 2	Yes	A1, B1, C1	Class 1	54 in	6.4 (217)	 	Knit Shirt

POLARTEC® POWER GRID™ FR

Utilizing Polartec's famous grid construction, Polartec® Power Grid™ FR is a jersey knit that provides superior warmth without weight, minimal bulk and the combined ability to both trap warm air and quickly release excess heat during high exertion.



Polartec® Power Grid™ FR Fabrics

STYLE	DESCRIPTION	CONTENT	NFPA 70E PPE CATEGORY	NFPA 2112 CERTIFIED	EN ISO 11612:2015	IEC 61482-2	CUTTABLE WIDTH	SPEC WEIGHT oz/yd ² (g/m ²)	LAUNDRY	TYPICAL GARMENT APPLICATIONS
2309/2309HV	9.6 oz Jersey Knit, Grid Velour CSA Z96 + ANSI 107	Lenzing™ Lyocell, Modacrylic, Aramid, Spandex	Cat 2	Yes	A1, B1, C2	Class 1	58 in	9.6 (325)	 	Lightweight Jacket, Balaclava

POLARTEC® WIND PRO® FR

A new standard in soft, weather-resistant FR fabric, Polartec® Wind Pro® FR is four times more wind resistant than classic fleece to reduce wind chill and repel moisture, while maintaining breathability and comfort.

Polartec® Wind Pro® FR Fabrics

STYLE	DESCRIPTION	CONTENT	NFPA 70E PPE CATEGORY	NFPA 2112 CERTIFIED	CUTTABLE WIDTH	SPEC WEIGHT oz/yd ² (g/m ²)	LAUNDRY	TYPICAL GARMENT APPLICATIONS
2510/2510HV	11.6 oz Jersey/Velour CSA Z96 + ANSI 107	Lenzing™ Lyocell, Modacrylic, Aramid, Spandex	Cat 2	Yes	58 in	11.6 (393)	 	Jacket

POLARTEC FR CARE INSTRUCTIONS

- Machine wash warm
- Tumble dry low
- Do not bleach
- Do not iron
- Do not dry clean
- Avoid the use of fabric softeners

The information in this publication is based on testing conducted by or conducted on behalf of Westex, Inc., a subsidiary of Milliken & Company, and represents our analysis of the test results. It is not intended to substitute for any testing that may be unique and necessary for your facility for you to determine the suitability of our products for your particular purpose. Since we cannot anticipate all variations in end-user conditions, Westex, Inc. makes no warranties and assumes no liability whatsoever in connection with any use of this information. As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Any test results reported are based on standard laboratory testing but should not be used to predict performance in actual fire situations. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing. Use caution near sources of flame or intense heat and do not launder with bleach or fabric softeners. Westex is a registered trademark of Milliken & Company.